



- Specified length A,B,C,D,E to be shown as last designator in the ordering number, example : 1N-CPHLN-A



Hex Long Nipple__NPT(M) x NPT(M)

COMFIT PRODUCT CODE	NPT MALE PIPE SIZE (N) (Inch)	(L) Available Length					HEX (F)	WORKING PRESSURE (PSIG) STAINLESS STEEL
		A	B	C	D	E		
		1-CPHLN	1/16					
2-CPHLN	1/8					7/16	9100	
4-CPHLN	1/4					5/8	7500	
6-CPHLN	3/8	1.50	2.00	2.50	3.00	3/4	7200	
8-CPHLN	1/2					7/8	6600	
12-CPHLN	3/4					1-1/8	6400	
16-CPHLN	1					1-3/8	4600	



Adapter__NPT(F) x NPT(M)



COMFIT PRODUCT CODE	NPT FEMALE (N)	NPT MALE (N1)	LENGTH (L)	HEX (F)	WORKING PRESSURE (PSIG) STAINLESS STEEL
	(Inch)				
2-CPA-2	1/8	1/8	1.03	5/8	6400
4-CPA-4	1/4	1/4	1.39	3/4	6600
6-CPA-6	3/8	3/8	1.44	7/8	5300
8-CPA-8	1/2	1/2	1.88	1-1/8	5200
12-CPA-12	3/4	3/4	2.02	1-3/8	4300
16-CPA-16	1	1	2.38	1-5/8	4500



Adapter__NPT(F) x ISOT(M)



COMFIT PRODUCT CODE	NPT FEMALE (N)	ISO (BSPP) MALE (N1)	LENGTH (L)	HEX (F)	LENGTH (L1)	WORKING PRESSURE (PSIG) STAINLESS STEEL
	(Inch)					
2-CPA-2RS	1/8	1/8	0.99	9/16	0.28	6100
4-CPA-4RS	1/4	1/4	1.31	3/4	0.44	6200
6-CPA-6RS	3/8	3/8	1.41	7/8	0.44	5000
8-CPA-8RS	1/2	1/2	1.74	1-1/8	0.56	4600
12-CPA-12RS	3/4	3/4	2.00	1-5/16	0.62	4300
16-CPA-16RS	1	1	2.10	1-5/8	0.72	4100

RS parallel threads are commonly used with flat RP gasket, please refer page no.29



Reducing Adapter__NPT(F) x NPT(M)

COMFIT PRODUCT CODE	NPT FEMALE (N)	NPT (N1)	LENGTH (L)	HEX (F)	Working Pressure (PSIG) STAINLESS STEEL
	(Inch)				
2-CPRA-1	1/8	1/16	1.03	5/8	6400
4-CPRA-1	1/4	1/16	1.20	3/4	6600
6-CPRA-1	3/8	1/16	1.25	7/8	5300
4-CPRA-2	1/4	1/8	1.20	3/4	6600
6-CPRA-2	3/8	1/8	1.25	7/8	5300
8-CPRA-2	1/2	1/8	1.50	1-1/8	5200
12-CPRA-2	3/4	1/8	1.56	1-3/8	4300
16-CPRA-2	1	1/8	1.81	1-5/8	4500
6-CPRA-4	3/8	1/4	1.44	7/8	5300
8-CPRA-4	1/2	1/4	1.69	1-1/8	5200
12-CPRA-4	3/4	1/4	1.75	1-3/8	4300
16-CPRA-4	1	1/4	2.00	1-5/8	4500
8-CPRA-6	1/2	3/8	1.69	1-1/8	5200
12-CPRA-6	3/4	3/8	1.75	1-3/8	4300
16-CPRA-6	1	3/8	2.00	1-5/8	4500
12-CPRA-8	3/4	1/2	1.94	1-3/8	4300
16-CPRA-8	1	1/2	2.19	1-5/8	4500
16-CPRA-12	1	3/4	2.19	1-5/8	4500
24-CPRA-12	1-1/2	3/4	2.48	2-3/8	
20-CPRA-16	1-1/4	1	2.53	2-1/8	
24-CPRA-16	1-1/2	1	2.65	2-3/8	
32-CPRA-16	2	1	2.68	2-7/8	



Gauge Adapter _ISOP (F) X NPT (M)

COMFIT PRODUCT CODE	ISO (BSPP) PARALLEL FEMALE (N1)	NPT MALE (N)	LENGTH (L)	HEX (F)	WORKING PRESSURE (PSIG) STAINLESS STEEL
	(Inch)				
2RG-CPGA-2	1/8	1/8	1.09	3/4	6100
4RG-CPGA-4	1/4	1/4	1.42	7/8	6200
6RG-CPGA-6	3/8	3/8	1.49	1-1/16	5000
8RG-CPGA-8	1/2	1/2	1.94	1-1/4	4600
12RG-CPGA-12	3/4	3/4	2.00	1-5/16	4300
16RG-CPGA-16	1	1	2.28	1-5/8	4100

DIMENSIONS FOR REFERENCE ONLY, SUBJECT TO CHANGE.